

## Enphase Envoy-S Metered

The **Enphase Envoy-S Metered™** communications gateway delivers solar production and energy consumption data to Enphase Enlighten™ monitoring and analysis software for comprehensive, remote maintenance and management of the Enphase System.

With production metering and consumption monitoring options, Envoy-S is the platform for total energy management and integrates with the Enphase AC Battery™.



### Smart

- Enables web-based monitoring and control
- Bidirectional communications for remote upgrades
- Power export limiting and phase imbalance management

### Simple

- Easy system configuration using the Enphase Installer Toolkit™ mobile app
- Flexible networking with Wi-Fi, Ethernet, or mobile
- DIN rail mount

### Reliable

- Designed for installation indoors or in an outdoor enclosure
- Five-year warranty

# Enphase Envoy-S Metered

<b>MODEL NUMBER</b>	
Envoy-S Metered - ENV-S-WM1-230	Enphase Envoy-S communications gateway with integrated PV and consumption metering. Includes two CTs (200A limit).
<b>ACCESSORIES (Order Separately)</b>	
Current transformers (CTs) CT-200-SPLIT	Lead length 4 m, extendable to 213 m depending on wire type (see installation manual). LxWxH: 50.8mm x 35.3mm x 60.5mm. Order extra CTs if monitoring multiple phases.
Enphase Mobile Connect™ CELLMODEM-02	Plug and play industrial grade mobile modem with five-year data plan for systems up to 60 microinverters. (Available where there is adequate mobile service in the installation area.)
Power line communications phase coupler LPC-01	Required for multi-phase systems
<b>POWER REQUIREMENTS</b>	
Hardwired	230 VAC or 400Y/230 VAC, 50 Hz Max 20A over current protection required
<b>CAPACITY</b>	
Number of microinverters polled	Up to 600
<b>MECHANICAL DATA</b>	
Dimensions (WxHxD)	213 x 126 x 45 mm
Weight	0.5 kg
Ambient temperature range	-40° to 65° C -40° to 46° C if installed in an enclosure
Environmental rating	IP30. For installation indoors or in an IP54-rated (or better) enclosure.
Altitude	To 2000 meters
USB ports	Two USB 2.0 ports, auto-sensing, auto-negotiation
<b>INTERNET CONNECTION OPTIONS</b>	
Integrated Wi-Fi	802.11b/g/n (2.4 GHz, 5 GHz)
Ethernet	Optional, 802.3, Cat5E (or Cat 6) UTP Ethernet cable (not included)
Mobile	Optional, CELLMODEM-02 (not included)
<b>COMPLIANCE</b>	
Compliance	IEC/EN 61010-1:2010, EN50065-1, EN61000-4-5, EN61000-6-1, EN61000-6-2, C-Tick
<b>ADVANCED FUNCTIONS<sup>1</sup></b>	
Power export limiting	Configurable for zero export when installed with S-Series microinverters
Phase imbalance management	Configurable for phase imbalance management when installed with S-Series microinverters

1. Software upgrade required for advanced function support.

To learn more about Enphase offerings, visit [enphase.com/au](http://enphase.com/au)

© 2016 Enphase Energy. All rights reserved. All trademarks or brands in this document are registered by their respective owner.  
2016-08-17

