

# GOODWE

## XS PLUS+ Series

0.7-3kW | Single Phase | 1 MPPT

GoodWe XS Plus+ series is an ultra-small residential solar inverter specifically designed to bring comfort and quiet operation as well as high efficiency to households. Its capacity ranges from 0.7kW to 3.0kW and its most outstanding characteristic is lightweight, which is only 5.8kg and as well as its extremely compact size equivalent to an A4 paper, that make it particularly easy to carry & install. Remarkably, it offers 130% of DC input oversizing, and it's able to achieve maximum European efficiency of 97.2% for maximum performance. Conveniently, the communication options available on this inverter are both LAN and Wi-Fi for smart home integration.



### Smart Control & Monitoring

- Load consumption monitoring
- Power export limit



### High Power Generation

- Up to 15A max. DC input current per string
- 40V start-up voltage



### Superb Safety & Reliability

- IP65 ingress protection
- Quality and robust components



### Friendly & Thoughtful Design

- Fanless design for quiet operation
- A4 size with light weight

Technical Data	GW700-XS-11	GW1000-XS-11	GW1500-XS-11	GW2000-XS-11	GW2500-XS-11	GW3000-XS-11
<b>Input</b>						
Max. Input Power (W)	945	1350	2025	2700	3375	4050
Max. Input Voltage (V)	500	500	500	500	600	600
MPPT Operating Voltage Range (V)	40 ~ 450	40 ~ 450	50 ~ 450	50 ~ 450	50 ~ 550	50 ~ 550
Start-up Voltage (V)	40	40	50	50	50	50
Nominal Input Voltage (V)	360					
Max. Input Current per MPPT (A)	15					
Max. Short Circuit Current per MPPT (A)	18.75					
Number of MPP Trackers	1					
Number of Strings per MPPT	1					
<b>Output</b>						
Nominal Output Power (W)	700	1000	1500	2000	2500	3000
Nominal Output Apparent Power (VA)	700	1000	1500	2000	2500	3000
Max. AC Active Power (W)	800	1100	1650	2200	2750	3300
Max. AC Apparent Power (VA)	800	1100	1650	2200	2750	3300
Nominal Output Voltage (V)	230	230	230	230	220 / 230	220 / 230
Output Voltage Range (V)	154 ~ 288					
Nominal AC Grid Frequency (Hz)	50 / 60					
AC Grid Frequency Range (Hz)	45 ~ 55 / 57 ~ 63					
Max. Output Current (A)	3.5	4.8	7.2	9.6	12	14.3
Power Factor	~1 (Adjustable from 0.8 leading to 0.8 lagging)					
Max. Total Harmonic Distortion	<3%					
<b>Efficiency</b>						
Max. Efficiency	97.2%	97.2%	97.3%	97.5%	97.6%	97.6%
European Efficiency	96.0%	96.4%	96.6%	97.0%	97.2%	97.2%
<b>Protection</b>						
PV Insulation Resistance Detection	Integrated					
Residual Current Monitoring	Integrated					
Anti-islanding Protection	Integrated					
AC Overcurrent Protection	Integrated					
AC Short Circuit Protection	Integrated					
AC Overvoltage Protection	Integrated					
DC Switch	Integrated					
DC Surge Protection	Type III (Type II Optional)					
AC Surge Protection	Type III					
AFCI	Optional					
<b>General Data</b>						
Operating Temperature Range (°C)	-25 ~ +60					
Relative Humidity	0 ~ 100%					
Max. Operating Altitude (m)	3000					
Cooling Method	Natural Convection					
User Interface	LED, LCD, WLAN + APP					
Communication	WiFi or LAN or RS485 (Optional)					
Weight (kg)	5.8					
Dimension (W x H x D mm)	295 x 230 x 113					
Noise Emission (dB)	<25	<25	<25	<25	<30	<30
Topology	Non-isolated					
Self-consumption at Night (W)	<1					
Ingress Protection Rating	IP65					
DC Connector	MC4 (2.5 ~ 4mm <sup>2</sup> )					
AC Connector	Plug and play connector					
Country of Manufacture	China					

\*: Please visit GoodWe website for the latest certificates.