



Three Phase Hybrid Inverter

SUN-10/12/15/20/25K-SG01HP3-AU-AM2



- 100** 100% unbalanced output, each phase
-  AC couple to retrofit existing solar system
- 16** Max. 16pcs parallel for on-grid and off-grid operation; Support multiple batteries parallel
- 50** Max. charging/discharging current of 50A
- H** High voltage battery, higher efficiency
- 6** 6 time periods for battery charging/discharging
-  Support storing energy from diesel generator

Deye

Stock Code: 605117.SH

Model	SUN-10K-SG01 HP3-AU-AM2	SUN-12K-SG01 HP3-AU-AM2	SUN-15K-SG01 HP3-AU-AM2	SUN-20K-SG01 HP3-AU-AM2	SUN-25K-SG01 HP3-AU-AM2
Battery Input Data					
Battery Type	Lithium-ion				
Battery Voltage Range (V)	160-700				
Max. Charging Current (A)	37			50	
Max. Discharging Current (A)	37			50	
Charging Strategy for Li-ion Battery	Self-adaption to BMS				
Number of Battery Input	1				
PV String Input Data					
Max. PV Input Power (W)	15000	18000	22500	30000	37500
Max. PV Input Voltage (V)	1000				
Start-up Voltage (V)	180				
MPPT Voltage Range (V)	150-850				
Rated PV Input Voltage (V)	600			700	
Max. Operating PV Input Current (A)	20+20	26+20		26+26	
Max. Input Short-Circuit Current (A)	30+30	39+30		39+39	
No. of MPP Trackers/ No. of Strings MPP Tracker	2/1+1	2/2+1		2/2+2	
AC Input/Output Data					
Rated AC Input/Output Active Power (W)	10000	12000	15000	20000	25000
Max. AC Input/Output Apparent Power (VA)	10000	12000	15000	20000	25000
Rated AC Input/Output Current (A)	14.5	17.4	21.8	29	36.3
Max. AC Input/Output Current (A)	14.5	17.4	21.8	29	36.3
Max. Continuous AC Passthrough (grid to load) (A)	40	80			
Peak Power (off-grid) (W)	1.5 times of rated power, 10s				
Power Factor Adjustment Range	0.8 leading to 0.8 lagging				
Rated Input/Output Voltage/Range (V)	230/400V 240/415V 0.85Un-1.1Un				
Rated Input/Output Grid Frequency/Range(Hz)	50Hz/45Hz-55Hz				
Grid Connection Form	3L+N+PE				
Total Current Harmonic Distortion THDi	<3% (of nominal power)				
DC Injection Current	<0.5% In				
Efficiency					
Max. Efficiency	97.6%				
Euro Efficiency	97.0%				
MPPT Efficiency	>99%				
Equipment Protection					
Integrated	DC Polarity Reverse Connection Protection, AC Output Overcurrent Protection, Thermal Protection, AC Output Overvoltage Protection, AC Output Short Circuit Protection, DC Component Monitoring, Overvoltage Load Drop Protection, Ground Fault Current Monitoring, Arc Fault Circuit Interrupter (optional), Power Network Monitoring, Island Protection Monitoring, Earth Fault Detection, DC Input Switch, DC Terminal Insulation Impedance Monitoring, Residual Current (RCD) Detection, Surge protection level				
Surge Protection Level	TYPE II(DC), TYPE II(AC)				
Interface					
Communication Interface	RS485/CAN				
Monitor Mode	GPRS/WIFI/Bluetooth/4G/LAN(optional)				
General Data					
Operating Temperature Range (°C)	-40 to +60°C, >45°C Derating				
Permissible Ambient Humidity	0-100%				
Permissible Altitude	2000m				
Noise (dB)	≤55				
Ingress Protection(IP) Rating	IP 65				
Inverter Topology	Transformerless				
Over Voltage Category	OVC II(DC), OVC III(AC)				
Cabinet Size (WxHxD mm)	408×638×237 (Excluding Connectors and Brackets)				
Weight (kg)	30.5				
Type of Cooling	Intelligent Air Cooling				
Warranty	10 Year				
Grid Regulation	AS/NZS 4777.2				
Safety / EMC Standard	IEC/EN 61000-6-1/2/3/4, IEC/EN 62109-1, IEC/EN 62109-2				