


Three Phase Hybrid Inverter

SUN-5/6/8/10/12K-SG04LP3-AU



- 100** 100% unbalanced output, each phase; Max. output up to 50% rated power
- AC** AC couple to retrofit existing solar system
- 16** Max. 16pcs parallel for on-grid and off-grid operation; Support multiple batteries parallel
- 240** Max. charging/discharging current of 240A
- 48** 48V low voltage battery, transformer isolation design
- 6** 6 time periods for battery charging/discharging
- Generator** Support storing energy from diesel generator

Deye

Stock Code: 605117.SH

Model	SUN-5K -SG04LP3-AU	SUN-6K -SG04LP3-AU	SUN-8K -SG04LP3-AU	SUN-10K -SG04LP3-AU	SUN-12K -SG04LP3-AU
Battery Input Data					
Battery Type	Lead-acid or Lithium-ion				
Battery Voltage Range (V)	40-60				
Max. Charging Current (A)	120	150	190	210	240
Max. Discharging Current (A)	120	150	190	210	240
Charging Strategy for Li-Ion Battery	Self-adaption to BMS				
Number of Battery Input	1				
PV String Input Data					
Max. PV access power(W)	10000	12000	16000	20000	24000
Max. DC Input Power (W)	7500	9000	12000	15000	18000
Rated PV Input Voltage (V)	800				
Start-up Voltage (V)	160				
MPPT Voltage Range (V)	200-650				
Rated DC Input Voltage(V)	550				
Max. Operating PV Input Current (A)	13+13			26+13	
Max. Input Short-Circuit Current (A)	19.5+19.5			39+19.5	
No. of MPP Trackers/ No. of Strings MPP Tracker	2/1+1			2/2+1	
AC Output Data					
Rated AC Output Active Power (W)	5000	6000	8000	10000	12000
Max AC Output Active Power (W)	5000	6000	8000	10000	12000
AC Output Rated Current (A)	7.2	8.7	11.6	14.5	17.4
Max. AC Output Current (A)	7.2	8.7	11.6	14.5	17.4
Max. Continuous AC Passthrough (A)	45				
Peak Power (off grid)	2 time of rated power, 10 S				
Power Factor Adjustment Range	0.8 leading to 0.8 lagging				
Rated Input/Output Voltage/Range (V)	230 /240 0.85Un-1.1Un				
Rated Input/Output Grid Frequency/Range	50Hz/45Hz-55Hz				
Grid Connection Form	3L+N+PE				
Total Harmonics Current Distortion (THDi)	<3% (of nominal power)				
DC Current Injection	<0.5% In				
Efficiency					
Max. Efficiency	97.60%				
Euro Efficiency	97.0%				
MPPT Efficiency	99.90%				
Protection					
Integrated	DC Polarity Reverse Connection Protection, AC Output Overcurrent Protection, Thermal Protection, AC Output Overvoltage Protection, AC Output Short Circuit Protection, DC Component Monitoring, Overvoltage Load Drop Protection, Ground Fault Current Monitoring, Arc Fault Circuit Interrupter (optional), Power Network Monitoring, Island Protection Monitoring, Earth Fault Detection, DC Input Switch, DC Terminal Insulation Impedance Monitoring, Residual Current (RCD) Detection, Surge protection level				
Over Voltage Category	TYPE II(DC), TYPE II(AC)				
Interface					
Communication Interface	RS485/CAN				
Monitor Mode	GPRS/WIFI/Bluetooth/4G/LAN(optional)				
General Data					
Operating Temperature Range (°C)	-40 to +60°C, >45°C derating				
Permissible Ambient Humidity	0-100%				
Permissible Altitude	2000m				
Inverter Topology (solar/battery)	Transformerless/ HF Transformer				
Over Voltage Category	OVC II(DC), OVC III(AC)				
Noise (dB)	<55 dB				
Weight (kg)	38				
Cabinet size (mm)	422W x 658H x254D (Excluding connectors and brackets)				
Protection Degree	IP65				
Type of Cooling	Intelligent Air Cooling				
Warranty	10 Years				
Grid Regulation	AS/NZS 4777.2				
Safety EMC / Standard	IEC/EN 61000-6-1/2/3/4, IEC/EN 62109-1, IEC/EN 62109-2				